



VoIP Adapter User Guide

FTA1101

Contents

About This User Guide.....	1
Contacting FlyingVoice.....	2
Purpose.....	2
Cross references.....	2
Feedback.....	2
Declaration of Conformity.....	3
Part 15 FCC Rules.....	3
Warnings and Notes.....	5
Warnings.....	5
Notes.....	5
Chapter 1 Product description.....	6
FTA1101.....	7
LED Indicators and Interfaces.....	8
Hardware Installation.....	9
Chapter 2 IVR Voice Prompt.....	11
Voice Gateway Configuration Method (IVR).....	12
Start IVR.....	12
IVR Description.....	12
Chapter 3 Basic Settings	18
Web Page.....	19
About Password.....	19
URL Format.....	19
WEB Interface Introduction.....	20
SIP Account configuration.....	22
Basic Function.....	23
Calling phone or extension numbers.....	23
Direct IP calls.....	23
Call Hold.....	23
Call transfer.....	23
Conference.....	24
Chapter 4 Web Interface	18
Login.....	26
Status.....	27
Network and Security.....	28
WAN.....	28
LAN.....	33
VPN.....	34
Port Forward.....	36
DMZ.....	37
DDNS.....	38
Port Setting.....	39
Routing.....	39
Advance.....	40
Wireless configuration.....	42
Wireless Security.....	45
Wi-Fi Repeater.....	48

WMM.....	51
WDS.....	52
Station Info.....	52
Advanced.....	53
SIP Account.....	55
SIP Settings.....	60
Phone.....	62
Preferences.....	62
Dial Rule.....	66
Blacklist.....	68
Call Log.....	69
Administration.....	70
Management	70
Firmware Upgrade.....	74
Scheduled Tasks.....	75
Provision.....	76
SNMP.....	77
TR-069.....	78
Diagnosis.....	79
Operating Mode.....	81
System Log.....	81
Logout.....	81
Reboot.....	81
Chapter 5 IPv6 address configuration.....	82
Introduction.....	83
IPv6 Advance.....	84
Configuring IPv6.....	84
Viewing WAN port status.....	85
IPv6 DHCP configuration for LAN/WLAN clients.....	85
LAN DHCPv6.....	86
Chapter 6 Troubleshooting Guide.....	87
Configuring PC to get IP Address automatically.....	88
Cannot connect to the Web.....	89
Forgotten Password.....	89

About This User Guide

FTA1101, which has one FXS port, one LAN port and one WAN port, is one of the most popular VoIP ATAs researched and produced by Flyingvoice. This product can not only provide one SIP lines for users to make calls, but also it Provides wired network connectivity, make you enjoy easy network atmosphere. What's more, FTA1101 support T.38 real time FAX and T.30 FAX with G.711. FTA1101 is a stand-alone device, which requires no PC to make Internet calls. This ATA guarantees clear and reliable voice quality on Internet, which is fully compatible with SIP industry standard and able to interoperate with many other SIP devices and software on the market. The Flyingvoice powerful VoIP ATA FTA1101, Users can also take FTA1101 as a FTP server, to share LAN files, pictures and other resources. Meanwhile, 1 FXS port can be well adapted to small and micro enterprises, FXS can work for telephone or for Fax, no need to add additional equipment. FTA1101 VoIP ATAs is ideally suited for small and medium enterprises (SMB) to build wireless office. The FTA1101 is based on SIP V2.0 and 802.11n standard and compatibility with most service providers. It features 1 phone port telephone ports, 2 10M/100M Ethernet ports which brings great



This guide contains the following chapters:

- [Chapter 1: Product description](#)
- [Chapter 2: Configuring IVR Voice Prompt](#)
- [Chapter 3: Configuring Basic Settings](#)
- [Chapter 4: Web Interface](#)
- [Chapter 5: IPv6 address configuration on WAN interface](#)
- [Chapter 6: Troubleshooting Guide](#)

Contacting FlyingVoice

Main website: <http://www.flyingvoice.com/>
Sales enquiries: sales1@flyingvoice.com
Support enquiries: support@flyingvoice.com
Hotline: 0755-26099365
Address: 1804, Building 1, Chongwen Park, Nanshan Zhiyuan, Nanshan District,
Shenzhen, China

Purpose

The documents are intended to instruct and assist personnel in the operation, installation and maintenance of the FlyingVoice equipment and ancillary devices. It is recommended that all personnel engaged in such activities be properly trained. FlyingVoice disclaims all liability whatsoever, implied or express, for any risk of damage, loss or reduction in system performance arising directly or indirectly out of the failure of the customer, or anyone acting on the customer's behalf, to abide by the instructions, system parameters, or recommendations made in this document.

Cross references

References to external publications are shown in italics. Other cross references, emphasized in blue text in electronic versions, are active links to the references.

This document is divided into numbered chapters that are divided into sections. Sections are not numbered, but are individually named at the top of each page, and are listed in the table of contents.

Feedback

We appreciate feedback from the users of our documents. This includes feedback on the structure, content, accuracy, or completeness of our documents. Send feedback to support@flyingvoice.com.

Declaration of Conformity

Part 15 FCC Rules

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



Caution

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Class B Digital Device or Peripheral

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment can generate, use and radiate radio frequency energy. If not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference does not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interferences by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

ISED Compliance Statements

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference.
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- (1) L'appareil ne doit pas produire de brouillage;
- (2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Cet équipement est conforme aux limites d'exposition aux radiations IC CNR-102 établies pour un environnement non contrôlé.

RF Exposure Compliance

This equipment complies with FCC/IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Cet équipement est conforme aux limites d'exposition aux radiations IC CNR-102 établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec une distance minimale de 20 cm entre le radiateur et votre corps. Cet émetteur ne doit pas être colocalisé ou fonctionner en conjonction avec une autre antenne ou un autre émetteur.

Warnings and Notes

The following describes how warnings and notes are used in this document and in all documents of the FlyingVoice document set.

Warnings

Warnings precede instructions that contain potentially hazardous situations. Warnings are used to alert the reader to possible hazards that could cause loss of life or physical injury. A warning has the following format:



Warning

Warning text and consequence for not following the instructions in the warning.

Notes

A note means that there is a possibility of an undesirable situation or provides additional information to help the reader understand a topic or concept. A note has the following format:



Notes

Notes text and consequence for not following the instructions in the Notes.

Chapter 1 Product description

This chapter covers:

- [FTA1101](#)
- [LED Indicators and Interfaces](#)
- [Hardware Installation](#)
- [Voice Prompt](#)


FTA1101

Table 1 Features at-a-glance

Port/Model	FTA1101	
picture (EU Plug)		
picture (US Plug)		
WAN	1	
LAN	1	
FXS	1	
Ethernet interface	2* RJ45 10/100M	
Fax	T.30, T.38 Fax	
Wire-speed NAT	Support	
Voice Code	G.711 (A-law, U-law), G.729A/B, G.723, G.722 (Wide band)	
Management	Voice menu, Web Management, Provision:TFTP/HTTP/HTTPS, TR069, SNMP	
VLAN	Support	

LED Indicators and Interfaces

Table 2 FTA1101 Interfaces



Interface	Description
PHONE	Analog phone connector
USB	Connect USB
WAN	Connector for accessing the Internet
LAN	Connectors for local networked devices

Hardware Installation

Before configuring your router, please see the procedure below for instructions on connecting the device in your network.

Procedure 1 Configuring the Router

1. Connect analog phone to ATA Port with an RJ11 cable.
2. Connect the WAN port to the Internet your network's modem/switch/router/ADSL
3. equipment using an Ethernet cable.
4. Connect one end of the power cord to the power port of the device. Connect the other end to the wall outlet.
5. Check the Power, WAN, and LAN LED to confirm network connectivity.



Warning

Please do not attempt to use unsupported power adapters and do not remove power during configuring or updating the device. Using other power adapters may damage



Warning

Changes or modifications not expressly approved by the party responsible for compliance can void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency cause harmful interference to radio communications. However, there is no energy and, if not installed and used in accordance with the instructions, may guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
 - Increase the separation between the equipment and receiver.
 - Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
-

Chapter 2 IVR Voice Prompt

This chapter contains:

- [Voice Gateway Configuration Method \(IVR\)](#)
- [IVR description](#)

Voice Gateway Configuration Method (IVR)

The device can be configured in two ways, as follows:

- (1) Use IVR (Interactive Voice Response)
- (2) the use of web pages

This chapter mainly introduces how to configure the voice gateway through IVR.

Start IVR

Users follow these steps to achieve IVR:

- (1) Go off-hook and press the "****" key to start the IVR. Then the user will hear the voice prompt "1 WAN port configuration...".
- (2) According to different options, press any digit between 0 and 9, the device will broadcast the corresponding content, the numbers 0 to 9 represent the details as shown in the chart below.
- (3) After each setting will play "Please input option, 1 WAN port configuration...".



Note

Before using IVR, please confirm analog phone is connected with ATA correctly.

IVR Description

The following chart lists the IVR requirements and a detailed description:




Table 3 IVR Menu Setting Options

Operation code	Menu
1 Network port configuration (1)WAN Port Configuration	- Pick up phone and press “****” to start IVR - Select "1", then the device will continue to broadcast to remind users to choose 1.WAN port connection type; 2.WAN port IP address; 3. WAN subnet mask; 4. Gateway; 5. DNS - Choose “1” , and The router reports the current WAN port connection type2) - Prompt "Please enter password" , user needs to input password and press “#” key, if user wants to configuration WAN port connection type. The password in IVR is same as web management interface login, the user may use phone keypad to enter password directly For example: WEB login password is “admin” , so the password in IVR is “admin” . The user may “23646” to access and then configure the WAN connection port. The unit reports “Operation Successful” if the password is correct. - Prompt "Please enter password" , user needs to input password and press “#” key if user wants to configuration WAN port connection type. - Choose the new WAN port connection type (1) DHCP or (2) Static The unit reports “Operation Successful” if the changes are successful. The router returns to the prompt “please enter your option ...”

(2)WAN Port IP Address	1. Pick up phone and press “****” to start IVR 2. Choose “2” , and The router reports current WAN Port IP Address 3. Input the new WAN port IP address and press “#” key: 4. Use “*” to replace “.” , for exampleuser can input 192*168*20*168 to set the new IP address 192.168.20.168 5. Press # key to indicate that you have finished 6. Report “operation successful” if user operation is ok. 7. To quit, enter “*” .
(3)WAN Port Subnet Mask	1. Pick up phone and press “****” to start IVR 2. Choose “3” , and router reports current WAN port subnet mask 3. Input a new WAN port subnet mask and press # key: 4. Use “*” to replace “.” , user can input 255*255*255*0 to set the new WAN port subnet mask 255.255.255.0 5. Press “#” key to indicate that you have finished 6. Report “operation successful” if user operation is ok. 7. To quit, enter “*” .
(4)Gateway	1. Pick up phone and press “****” to start IVR 2. Choose “4” , and the router reports current gateway 3. Input the new gateway and press “#” key: 4. Use “*” to replace “.” , user can input 192*168*20*1 to set the new gateway 192.168.20.1. 5. Press “#” key to indicate that you have finished. 6. Report “operation successful” if user operation is ok. 7. To quit, press “*” .

(5)DNS	1. Pick up phone and press “****” to start IVR 2. Choose “5” , and the router reports current DNS 3. Input the new DNS and press # key: 4. Use “*” to replace “.” , user can input 192*168*20*1 to set the new gateway 192.168.20.1. 5. Press “#” key to indicate that you have finished.
2 Phone port Configuration	1. Pick up phone and press “****” to start IVR Choose “2” , and the router reports current “Phone port Configuration” 2. Select "2", then the device will continue to broadcast prompts the user to select 1. current phone number; 2. registration server address; 3. registration port; 4. call forwarding configuration; 3. Continue pressing "1" and the unit will continue to broadcast the phone number of the current phone port. The device will then broadcast "1. Phone number ..." again.
3 Factory Reset	1. Pick up phone and press “****” to start IVR 2. Choose “3” , and the router reports “Factory Reset” 3. Prompt "Please enter password", the method of inputting password is the same as operation 1. 4. If you want to quit, press “*” . 5. Prompt “operation successful” if password is right and then the router
4 Reboot	1. Pick up phone and press “****” to start IVR 2. Choose “4”, and the router reports “Reboot” 3. Prompt "Please enter password", the method of inputting password is same as operation 1. 4. the router reboots if password is right and operation

5 WAN Port Login	1. Pick up phone and press “****” to start IVR 2. Choose “5”, and the router reports “WAN Port Login” 3. Prompt "Please enter password", the method of inputting password is same as operation 1. 4. If user wants to quit, press “*”.
6 WEB Access Port	1. Pick up phone and press “****” to start IVR 2. Choose “6”, and the router reports “ WEB Access Port” 3. Prompt “Please enter password”, the method of inputting password is same as operation 1. 4. Report “operation successful” if user operation is ok.
7 Firmware Version	1. Pick up phone and press “****” to start IVR 2. Choose “7” and the router reports the current Firmware version



Note

1. While using Voice menu, press * (star) to return to main menu.
2. If any changes made in the IP assignment mode, the router must be rebooted in order for the settings to take effect.
3. While entering an IP address or subnet mask, use "*" (star) to enter "." (Dot) and use "#" (hash) key to finish entering IP address or subnet mask:
4. For example, to enter the IP address 192.168.20.159 by keypad, press these keys: 192*168*20*159, use the # (hash) key to indicate that you have finished entering the IP address.
5. Use the # (hash) key to indicate that you have finished entering the IP address or subnet mask
6. While assigning an IP address in Static IP mode, setting the IP address, subnet mask and default gateway is required to complete the configuration. If in DHCP mode, please make sure that a DHCP server is available in your existing broadband connection to which WAN port of FTA1101 is connected.
7. The default LAN port IP address of FTA1101 is 192.168.1.1 and this address should not be assigned to the WAN port IP address of FTA1101 in the same network segment of LAN port.
8. The password can be entered using phone keypad, the mapping table between number and letters as follows:

To input: D, E, F, d, e, f -- press '3'

To input: G, H, I, g, h, i -- press '4'

To input: J, K, L, j, k, l -- press '5'

To input: M, N, O, m, n, o -- press '6'

To input: P, Q, R, S, p, q, r, s -- press '7'

To input: T, U, V, t, u, v -- press '8'

To input: W, X, Y, Z, w, x, y, z -- press '9'

To input all other characters in the administrator password----press '0'.

Chapter 3 Basic Settings

This chapter covers:

- [Two-Level Management](#)
- [Web Management Interface](#)
- [Configuring](#)
- [Making a Call](#)

Web Page

About Password

Our device supports two levels of management: administrators and users.

(1) Administrator mode can browse and set all configuration parameters.

(2) User mode can set all configuration parameters except SIP1 that some parameters can not be changed, such as server address and port.

- Default user with administrator mode: Username: admin, Password: admin or XXXXXXXX

TIPS: Before June 2026, the default password is "**admin**". After June 2026: Default password is "XXXXXXXX" (shown on the device label, for devices with serial numbers FLY08426600001 and later)

- Default user with user/useradmin mode: Username: user/useradmin, Password: admin;

URL Format

FTA1101 has a built-in web server in response to HTTP get / post requests. Users can use a web browser, such as Microsoft's IE, to log in to the FTA1101 page and configure the FTA1101.

LAN port Login

1.Ensure your PC is connected to the router's LAN port correctly.



Note

You may either set up your PC to get an IP dynamically from the router or set up the IP address of the PC to be the same subnet as the default IP address of router is 192.168.30.1 (Depends on the IP address on the device label, before June 2026, the LAN port IP address is 192.168.1.1). For detailed information, see Chapter 5: Troubleshooting Guide.

2.Open a web browser on your PC and input "**http://192.168.30.1**" or "**http://192.168.1.1**"

3.The following window appears and prompts for username , password.

VoIP ... control panel

Username

Password

4.For administrator mode operation, please type username: **admin**, password: **admin** or **XXXXXXXX** and click Login to begin configuration. (XXXXXXXX is the Password shown on the Device Label)

5.For user or other mode operation, please type **user/admin** or **useradmin/admin** and click Login to begin configuration.



Note

If you are unable to access the web configuration, please see Chapter 5: Troubleshooting Guide for more information.

6.The web management interface automatically logs out the user after 5 minutes of inactivity.

WAN port Login

- 1.Ensure your PC is connected to the router’s WAN port correctly.
- 2.Obtain the IP addresses of WAN port using Voice prompt or by logging into the device web management interface via a LAN port and navigating to Network > WAN.
- 3.Open a web browser on your PC and input http://<IP address of WAN port>. The following login page will be opened to enter username and password.



- 4.For administrator mode operation, please type username: **admin**, password: **admin or XXXXXXXX** and click Login to begin configuration. (XXXXXXXX is the Password shown on the Device Label)
- 5.For user or other mode operation, please type **user/admin** or **useradmin/admin** and click Login to begin configuration.



Note

If you fail to access to the web configuration, see Chapter 6: Troubleshooting Guide for more information.

6.The web management interface automatically logs out the user after 5 minutes of inactivity.

WEB Interface Introduction

Table 4 WEB Interface Introduction

The screenshot shows the VoIP control panel interface. At the top right, it displays 'Firmware Version V3.2', 'Current Time 2017-11-13 16:16:0', and 'Admin Mode' with buttons for '[Logout]' and '[Reboot]'. The main navigation bar includes tabs for 'Status', 'Network', 'Wireless', 'SIP Account', 'Phone', and 'Administration' (labeled 1). Below this is a sub-navigation bar with 'Basic', 'LAN Host', and 'Syslog' (labeled 2). The 'Product Information' section (labeled 3) contains a table of device details. To the right, there is a 'Help' section (labeled 6) with links for 'Product Information', 'Line Status', 'Network Status', and 'System Status'. The 'Product Information' table lists fields like Product Name, MAC Addresses, and Versions. The 'Help' section provides brief descriptions for each status link.

Serial number	Name	Description
Postition 1	navigation bar	Click navigation bar, many sub-navigation bar will appear in the place 2
Postition 2	sub-navigation bar	Click sub-navigation bar to enter to configuration page
Postition 3	configuration title	The configuration title
Postition 4	configuration bars	The configuration bars
Postition 5	main information	Display the firmware version, DSP version, Current Time, and user can change login level (mode) to return to login page by press blue Switch button.
Postition 6	Help	Display the main information for configuration; user can get help from it directly.

Serial number	Name	Description
Postition 1	navigation bar	Click navigation bar, many sub-navigation bar will appear in the place 2
Postition 2	sub-navigation bar	Click sub-navigation bar to enter to configuration page
Postition 3	configuration title	The configuration title
Postition 4	configuration bars	The configuration bars
Postition 5	main information	Display the firmware version, DSP version, Current Time, and user can change login level (mode) to return to login page by press blue Switch button.
Postition 6	Help	Display the main information for configuration; user can get help from it directly.
	Save & Apply	Use this button,conifg will be saved
	Save	After changing the parameters, you need to click this button to save. After you click Save, there is a need to restart the device.
	Cancel	Click to cancel the change
	Reboot	Click to restart
	Refresh	Refresh current page

SIP Account configuration

FTA1101 have 1 Line to make SIP (Session Initiation Protocol) calls. Before registering, the device user should have a SIP account configured by the system administrator or provider. See the section below for more information.

Table 5 Config SIP the Web Management Interface

Status	Network	Wireless	SIP Account	Phone	Administration
Line 1	SIP Settings	VoIP QoS			
Basic					
Basic Setup					
Line Enable		Enable ▼		Outgoing Call without Registration	
				Disable ▼	
Proxy and Registration					
Proxy Server				Proxy Port	
				5060	
Outbound Server				Outbound Port	
				5060	
Backup Outbound Server				Backup Outbound Port	
				5060	
Allow DHCP Option 120 to Override SIP Server		Disable ▼			
Subscriber Information					
Display Name				Phone Number	
Account				Password	

Steps:

- Step 1. The account enable is set to "On" and the line can be used after opening.
- Step 2. The registration server fills in the IP address of the SIP server.
- Step 3. Display Name Fill in the content is the name of the number displayed on the LCD.
- Step 4. The registration account is filled with the account provided by the SIP server.
- Step 5. The name of the authentication is the SIP account provided by the SIP server.
- Step 6. The password is filled with the password provided by the SIP server registration account.
- Step 7. When you are finished, click the Save button at the bottom of the page to make the configuration take effect.
- Step 8. Check the registration of the corresponding line on the display / web status page.



Notes

Step 3-9 is to fill in the required content, other parameters fill in the required

Procedure

To view the SIP account status of device, open the **Status** web page and view the value of registration status.

Basic Function

Calling phone or extension numbers

To make a phone or extension number call:

- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) must have public IP addresses, or
- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) are on the same LAN using private or public IP addresses, or
- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) can be connected through a router using a public or private IP addresses.

To make a call, first pick up the analog phone or turn on the speakerphone on the analog phone, input the IP address directly, end with #.

Direct IP calls

Direct IP calling allows two phones, that is, an ATA with an analog phone and another VoIP Device, to talk to each other without a SIP proxy. VoIP calls can be made between two phones if:

- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) have public IP addresses, or
- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) are on the same LAN using private or public IP addresses, or
- Both ATA and the other VoIP device (i.e., another ATA or other SIP products) can be connected through a router using public or private IP addresses.

To make a direct IP call, first pick up the analog phone or turn on the speakerphone on the analog phone, Input the IP address directly, with the end “#” .

Call Hold

While in conversation, pressing the “*77” to put the remote end on hold, then you will hear the dial tone and the remote party will hear hold tone at the same time.

Pressing the “*77” again to release the previously hold state and resume the bi-directional media.

Call transfer

1. Blind Transfer

Chapter 3: Basic Settings

Assume that call party A and party B are in conversation. Party A wants to Blind Transfer B to C:

Party A dials “*78” to get a dial tone, then dials party C’s number, and then press immediately key # (or wait for 4 seconds) to dial out. A can hang up.

2.Attended Transfer

Assume that call party A and B are in a conversation. A wants to Attend Transfer B to C:

Party A dials “*77” to hold the party B, when hear the dial tone, A dials C’s number, then party A and party C are in conversation.

Party A dials “*78” to transfer to C, then B and C now in conversation.

If the transfer is not completed successfully, then A and B are in conversation again.

Conference

Assume that call party A and B are in a conversation. A wants to add C to the conference:

Party A dials “*77” to hold the party B, when hear the dial tone, A dial C’s number, then party A and party C are in conversation.

Party A dials “*88” to add C, then A and B, for conference.

Chapter 4 Web Interface

This chapter guides users to execute advanced (full) configuration through admin mode operation.

This chapter covers:

- [Login](#)
- [Status](#)
- [Network and Security](#)
- [Wireless](#)
- [SIP](#)
- [Phone](#)
- [Security](#)
- [Application](#)
- [Administration](#)
- [Management](#)
- [System Log](#)
- [Logout](#)
- [Reboot](#)

Login

Table 6 Login details



The screenshot displays the login page of a VoIP control panel. At the top, the text 'VoIP' is shown in green, followed by '... control panel' in blue. Below this, there is a login form with two input fields: 'Username' with the value 'admin' and 'Password' with masked characters '.....'. A 'Login' button is located to the right of the password field.

Procedure

1. Connect the LAN port of the router to your PC an Ethernet cable
2. Open a web browser on your PC and type http://"IP Address" (depends on the IP address on the device label)
3. Enter Username *admin* and Password *admin* or *XXXXXXXX* (Depends on the Password on the device label).
4. Click Login

Status

This webpage shows the status information about the Product, Network, SIP Account Status, FXS Port Status, Network Status, Wireless Info and System Status

Status

Network

Wireless

SIP Account

Phone

Administration

Basic

LAN Host

Syslog

Product Information

Product Information

Product Name	FTA1101
Internet(WAN) MAC Address	00:21:F2:10:CC:1D
PC(LAN) MAC Address	00:21:F2:10:CC:1C
Hardware Version	V2.1
Loader Version	V3.34(May 23 2017 20:27:20)
Firmware Version	V3.20(201706140611)
Serial Number	FLY84171000008

Line Status

Line Status

Line 1 Status	Register Fail
Primary Server	0.0.0.0
Backup Server	0.0.0.0

Network and Security

You can configure the WAN port, LAN port, DDNS, Multi WAN, DMZ, MAC Clone, Port Forward and other parameters in this section of the web management interface.

WAN

This page allows you to set WAN configuration with different modes. Use the Connection Type drop down list to choose one WAN mode and then the corresponding page will be displayed.

1.Static IP

This configuration may be utilized when a user receives a fixed public IP address or a public subnet, namely multiple public IP addresses from the Internet providers. In most cases, a Cable service provider will offer a fixed public IP, while a DSL service provider will offer a public subnet. If you have a public subnet, you can assign an IP address to the WAN interface.

Table 7 Internet

StatusNetworkWirelessSIP AccountPhoneAdministration

WANLANIPv6 AdvancedIPv6 WANIPv6 LANVPNPort ForwardDMZDDNSPort Setting

Eoip Tunnel

INTERNET

WAN

Connect Name1_MANAGEMENT_VOICE_INTERNET_R_VIDDelete Connect

ServiceMANAGEMENT_VOICE_INTERNET

IP Protocol VersionIPv4

WAN IP ModeStatic

MAC Address CloneDisable

NAT EnableEnable

VLAN ModeDisable

VLAN ID1(1-4094)

Static

IP Address192.168.10.223

Subnet Mask255.255.255.0

Default Gateway192.168.10.1

DNS ModeManual

Primary DNS192.168.10.1

Secondary DNS192.168.18.1

Port Bind

☒ Port_1

☒ Wireless(SSID)

☒ Wireless(SSID1)

☒ Wireless(SSID2)

☒ Wireless(SSID3)

Note : WAN connection can not be shared between the binding port , and finally bound port WAN connections bind operation will wash away before the other WAN connection to the port binding operation !

Field Name	Descripti
IP Address	The IP address of Internet port
Subnet Mask	The subnet mask of Internet port
Default Gateway	The default gateway of Internet port
DNS Mode	Select DNS mode, options are Auto and Manual: 1. When DNS mode is Auto, the device under LAN port will automatically obtain the preferred DNS and alternate DNS. 2. When DNS mode is Manual, the user manually configures the
Primary DNS Address	The primary DNS of Internet port
Secondary DNS Address	The secondary DNS of Internet port

2.DHCP

The Router has a built-in DHCP server that assigns private IP address to each local client.

The DHCP feature allows to the router to obtain an IP address automatically from a DHCP server. In this case, it is not necessary to assign an IP address to the client manually.

Table 8 DHCP

Status	Network	Wireless	SIP Account	Phone	Administration
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN
Port Forward					
DMZ					
DDNS					
Port Setting					
Eoip Tunnel					

INTERNET

WAN

Connect Name: 1_MANAGEMENT_VOICE_INTERNET_R_VID ▼ Delete Connect
Service: MANAGEMENT_VOICE_INTERNET ▼
IP Protocol Version: IPv4 ▼

WAN IP Mode: DHCP ▼
DHCP Server:

MAC Address Clone: Disable ▼
NAT Enable: Enable ▼
VLAN Mode: Disable ▼
VLAN ID: 1 (1-4094)
DNS Mode: Manual ▼
Primary DNS:
Secondary DNS:
DHCP
DHCP Renew: Renew
DHCP Vendor(Optional 60): FLYINGVOICE-FTA1101

Field Name	Description
DNS Mode	Select DNS mode, options are Auto and Manual:
	When DNS mode is Auto, the device under LAN port will automatically obtain the preferred DNS and alternate DNS.
	When DNS mode is Manual, the user should manually configure the preferred DNS and alternate DNS
Primary DNS Address	Primary DNS of Internet port.
Secondary DNS Address	Secondary DNS of Internet port.
DHCP Renew	Refresh the DHCP IP address
DHCP Vendor (Option60)	Specify the DHCP Vendor field. Display the vendor and product name.

3.PPPoE

PPPoE stands for Point-to-Point Protocol over Ethernet. It relies on two widely accepted standards: PPP and Ethernet. It connects users through an Ethernet to the Internet with a common broadband medium, such as a single DSL line, wireless device or cable modem. All the users over the Ethernet can share a common connection.

PPPoE is used for most of DSL modem users. All local users can share one PPPoE connection for accessing the Internet. Your service provider will provide you information about user name, password, and authentication mode.

Table 9 PPPoE

The screenshot shows the 'WAN' configuration page. The 'INTERNET' tab is selected. The 'WAN IP Mode' is set to 'PPPoE'. The 'PPPoe' section is highlighted with a red box and contains the following fields:

- PPPoe Account: [Text input field]
- PPPoe Password: [Text input field with masked characters]
- Confirm Password: [Text input field with masked characters]
- Service Name: [Text input field]

Below the Service Name field, there is a note: "Leave empty to autodetect".

Field Name	Descr
PPPoE Account	Enter a valid user name provided by the ISP
PPPoE Password	Enter a valid password provided by the ISP. The password can contain special characters and allowed special characters are \$, +, *, #, @ and ! For example, the password can be entered as #net123@IT!\$+*.
Confirm Password	Enter your PPPoE password again
Service Name	Enter a service name for PPPoE authentication. If it is left empty, the service name is auto detected.
Operation Mode	Select the mode of operation, options are Keep Alive, On Demand and Manual: When the mode is Keep Alive, the user sets the 'keep alive redial period'
Keep Alive Redial	Set the interval to send Keep Alive messaging
PPPoE Account	Assign a valid user name provided by the ISP

4. Bridge Mode

Bridge Mode under Multi WAN is different with traditional bridge setting. Bridge mode employs no IP addressing and the device operates as a bridge between the WAN port and the LAN port. Route Connection has to be built to give IP address to local service on device.

Table 10 Bridge Mode

INTERNET

WAN

Connect Name

Service

IP Protocol Version

WAN IP Mode

Bridge Type

DHCP Service Type

VLAN Mode

VLAN ID

1_MANAGEMENT_VOICE_INTERNET_R_VID ▾

MANAGEMENT_VOICE_INTERNET ▾

IPv4 ▾

Bridge ▾

IP Bridge ▾

Pass Through ▾

Disable ▾

1 (1-4094)

Delete Connect

Port Bind

☒ Port_1
☒ Wireless(SSID)

☒ Port_2
☒ Wireless(SSID1)

☒ Port_3
☒ Wireless(SSID2)

☒ Wireless(SSID3)

Note : WAN connection can not be shared between the binding port , and finally bound port WAN connections bind operation will wash away before the other WAN connection to the port binding operation !

Field Name	Descrip
Bridge Type	
IP Bridge	Allow all Ethernet packets to pass. PC can connect to upper network
PPPoE Bridge	Only Allow PPPoE packets pass. PC needs PPPoE dial-up software.
Hardware IP Bridge	Packets pass through hardware switch with wired speed. Does not support wireless port binding
DHCP Service Type Select DHCP Service Type	
Pass Through	DHCP packets can be forwarded between WAN and LAN, DHCP server in gateway will not allocate IP to clients of LAN port.
DHCP Snooping	When gateway forwards DHCP packets form LAN to WAN it will add option82 to DHCP packet, and it will remove option82 when forwarding DHCP packet from the WAN interface to the LAN interface. Local DHCP service will not allocate IP to clients of LAN port.

Local Service	Gateway will not forward DHCP packets between LAN and WAN, it also blocks DHCP packets from the WAN port. Clients connected to the LAN port can get IP from DHCP server run in gateway.
VLAN Mode	Enable or disable the VLAN mode.
Disable	The WAN interface is untagged. LAN is untagged.
Enable	The WAN interface is tagged. LAN is untagged.
Trunk	Only valid in bridge mode. All ports, including WAN and LAN, belong to this VLAN Id and all ports are tagged with this VLAN id. Tagged packets can pass through WAN and LAN.
VLAN ID	Set the VLAN ID.
802.1p	Set the priority of VLAN, Options are 0~7.

**Note**

Multiple WAN connections may be created with the same VLAN ID

LAN

LAN Port

NAT translates the packets from public IP address to local IP address to forward packets to the proper destination.

Table 11 LAN port

Status	Network	Wireless	SIP Account	Phone	Administration
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN
Port Forward					
DMZ					
DDNS					
Port Setting					
Eoip Tunnel					

PC Port(LAN)

PC Port(LAN)

Local IP Address	192.168.1.1
Local Subnet Mask	255.255.255.0
Local DHCP Server	Enable ▼
DHCP Start Address	192.168.1.2
DHCP End Address	192.168.1.254
DNS Mode	Auto ▼
Primary DNS	192.168.1.1
Secondary DNS	192.168.10.1
Client Lease Time(0-86400s)	86400
DHCP Client List	

DHCP Static Allotment

NO.	MAC	IP Address
Delete Selected	Add	Edit

Field Name	Description
IP Address	Enter the IP address of the router on the local area network. All the IP addresses of the computers which are in the router's LAN must be in the same network segment with this address, and the default gateway of the computers must be this IP address. (The default is
Local Subnet Mask	Enter the subnet mask to determine the size of the network (default is 255.255.255.0/24).
Local DHCP Server	Enable/Disable Local DHCP Server.
DHCP Start Address	Enter a valid IP address as a starting IP address of the DHCP server, and if the router's LAN IP address is 192.168.11.1, starting IP address can be 192.168.11.2 or greater, but should be less than the ending IP address.
DHCP End Address	Enter a valid IP address as an end IP address of the DHCP server.
DNS Mode	Select DNS mode, options are Auto and Manual: When DNS mode is Auto, the device under LAN port will automatically obtains the preferred DNS and alternate DNS. When DNS mode is Manual, the user should manually configure the preferred DNS and alternate DNS.
Primary DNS	Enter the preferred DNS address.
Secondary DNS	Enter the secondary DNS address.
Client Lease Time	This option defines how long the address will be assigned to the computer within the network. In that period, the server does not assign the IP address to the other computer.
DNS Proxy	Enable or disable; If enabled, the device will forward the DNS request of LAN-side network to the WAN side network.

VPN

VPN is a technology that builds a private network on a public network. The connection between any two nodes of the VPN network does not have the end-to-end physical link required by the traditional private network, but rather the network platform provided by the public network service provider, and the user data is transmitted in the logical link. With VPN technology, you can establish private connections and transfer data between any two devices on the public network.

Table 12 PPTP

StatusNetworkWirelessSIP AccountPhoneAdministration

WANLANIPv6 AdvancedIPv6 WANIPv6 LANVPNPort ForwardDMZDDNSPort Setting

Eoip Tunnel

VPN Settings

Administration

VPN Enable

PPTP

Initial Service IP

User Name

Password

.....

VPN As Default Route

Disable

MPPE Stateful

Disable

Require MPPE

Disable

Parameters name	Description
VPN Enable	Whether to enable VPN. Select PPTP mode.
Initial Service IP	The IP address of the VPN server.
User Name	The user name required for authentication.
Password	The password required for authentication.
VPN As Default Route	Prohibited or open, the default is prohibited.
MPPE Stateful	Enable or Disable MPPE Stateful.
Require MPPE	Enable or Disable Require MPPE.

Table 13 L2TP

StatusNetworkWirelessSIP AccountPhoneAdministration

WANLANIPv6 AdvancedIPv6 WANIPv6 LANVPNPort ForwardDMZDDNSPort Setting

Eoip Tunnel

VPN Settings

Administration

VPN Enable

L2TP

Initial Service IP

User Name

Password

.....

L2TP Tunnel Name

L2TP Tunnel Password

.....

VPN As Default Route

Disable

Parameters name	Description
VPN Enable	Whether to enable VPN. Select PPTP mode.
Initial Service IP	The IP address of the VPN server.
User Name	The user name required for authentication.
Password	The password required for authentication.
L2TP Tunnel Name	L2TP Tunnel Name
L2TP Tunnel	L2TP Tunnel Password
VPN As Default	Prohibited or open, the default is prohibited.

Table 14 OpenVPN

Status	Network	Wireless	SIP Account	Phone	Administration				
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN	Port Forward	DMZ	DDNS	Port Setting
Eoip Tunnel									
VPN Settings									
Administration									
VPN Enable OpenVPN ▼ OpenVPN TLS Auth Enable ▼ VPN As Default Route Disable ▼									
Parameters name	Description								
VPN Enable	Whether to enable VPN. Select OpenVPN mode.								
OpenVPN TLS Auth	Whether OpenVPN TLS authentication is enabled								
VPN As Default Route	Prohibited or open, the default is prohibited.								

Port Forward

Table 15 Port Forward

Status	Network	Wireless	SIP Account	Phone	Administration
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN
Port Forward DMZ DDNS Port Setting Routing Advance					
Eoip Tunnel					

Port Forwarding				
No.	Comment	IP Address	Port Range	Protocol
Delete Selected Add Edit				
Port Forwarding Comment IP Address Port Range Protocol (The maximum rule count is 32) Apply Cancel				

Virtual Servers					
No.	Comment	IP Address	Public Port	Private Port	Protocol
Delete Selected Add Edit					
Virtual Servers Comment IP Address Public Port Private Port Protocol (The maximum rule count is 32) Apply Cancel					

Field Name	Description
Comment	Sets the name of a port mapping rule or comment
IP Address	The IP address of devices under the LAN port
Port Range	Set the port range for the devices under the LAN port. (1-65535)
Protocol	You can select TCP, UDP, TCP & UDP three cases
Apply/Cancel	After finish configurations, click apply, the number will be generated under NO. List; click Cancel to if you do not want to make the changes
Comment	To set up a virtual server notes
IP Address	Virtual server IP address
Public Port	Public port of virtual server
Private Port	Private port of virtual servers ports
Protocol	You can select from TCP, UDP, and TCP&UDP
Apply/Cancel	After finish configurations, click apply, the number will be generated under NO. List; click Cancel to if you do not want to make the changes

DMZ

Table 16 DMZ



Demilitarized Zone (DMZ)	
DMZ Setting	
DMZ Enable	Enable ▼
DMZ Host IP Address	

Field Name	Description
DMZ Enable	Enable/Disable DMZ.
DMZ Host IP Address	Enter the private IP address of the DMZ host.

DDNS

Table 17 DDNS



DDNS Setting	
DDNS Setting	
Dynamic DNS Provider	None ▼
Account	
Password	
DDNS URL	
Status	NONE

Field Name	Description
Dynamic DNS Provider	DDNS is enabled and select a DDNS service provider.
Account	Enter the DDNS service account.
Password	Enter the DDNS service account password.
DDNS URL	Enter the DDNS domain name or IP address.
Status	See if DDNS is successfully upgraded.

Port Setting

Table 18 Port setting

Port Setting

WAN Port Speed Nego Auto ▼

LAN1 Port Speed Nego Auto ▼

Field Name	Description
WAN Port speed Nego	Auto-negotiation, options are Auto, 100M full, 100M half-duplex, 10M half and full.
LAN1 Port Speed Nego	Auto-negotiation, options are Auto, 100M full, 100M half, 10M half and 10M full.

Routing

Table 19 Routing

Static Routing Settings Help

Add or remove Internet n here.

Add a routing rule

Destination

Host/Net Host ▼

Gateway

Interface LAN ▼

Comment

Apply Reset

Current Routing Table in the system

No.	Destination	Mask	Gateway	Flags	Metric	Interface	Comment
Delete Selected Reset							

Field Name	Description
Destination	Destination address
Host/Net	Both Host and Net selection

Gateway	Gateway IP address
Interface	LAN/WAN/Custom three options, and add the corresponding address
Comment	Comment

Advance

Table 20 Advance

Status	Network	Wireless	SIP Account	Phone	Administration
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN
Port Forward	DMZ	DDNS	Port Setting	Routing	Advance
Eoip Tunnel					
Most Nat connections(512-8192)		4096		Help	
Mss Mode		☒ Manual ☐ Auto			
Mss Value(1260-1460)		1440			
AntiDos-P		☒ Enable ☐ Disable			
IP conflict detection		☒ Enable ☐ Disable			
IP Conflict Detecting Interval(0-3600s)		600			

Field Name	Description
Most Nat connections	The largest value which the FWR8401 can provide
Mss Mode	Choose Mss Mode from Manual and Auto
Mss Value	Set the value of TCP
AntiDos-p	You can choose to enable or prohibit
IP conflict detection	Select enable if enabled, phone IP conflict will have tips or prohibit;
IP conflict Detecting Interval	Detect IP address conflicts of the time interval

Eoip Tunnel

Table 21 Eoip Tunnel

Status	Network	Wireless	SIP	FXS1	FXS2	Security	Application	Administration		
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN	Port Forward	DMZ	VLAN	DDNS	QoS
Advance	Eoip Tunnel									

Eoip Tunnel

Eoip Tunnel

Eoip Tunnel 1	☐ Enable ☒ Disable
Remote IP Address	0.0.0.0
Eoip Tunnel 2	☐ Enable ☒ Disable
Remote IP Address	0.0.0.0
Eoip Tunnel 3	☐ Enable ☒ Disable
Remote IP Address	0.0.0.0
Eoip Tunnel 4	☐ Enable ☒ Disable
Remote IP Address	0.0.0.0
Eoip Tunnel 5	☐ Enable ☒ Disable
Remote IP Address	0.0.0.0

Field Name

Description

Eoip Tunnel 1-5	Choose to enable or disable the tunnel
Remote Address	Input requires a remote IP address

Wireless configuration


Basic

Table 22 Basic

Status	Network	Wireless	SIP Account	Phone	Administration
Basic	Wireless Security	WMM	WDS	WPS	Station Info
Advanced					

Basic Wireless Settings	
Wireless Network	
Radio On/Off	Radio On ▼
Wireless Connection Mode	AP ▼
Network Mode	11b/g/n mixed mode ▼
Multiple SSID	FTA1101-10CC1C Enable ☒ Hidden ☐ Isolated ☐ Max Client 16
Multiple SSID1	_____ Enable ☐ Hidden ☐ Isolated ☐ Max Client 16
Multiple SSID2	_____ Enable ☐ Hidden ☐ Isolated ☐ Max Client 16
Multiple SSID3	_____ Enable ☐ Hidden ☐ Isolated ☐ Max Client 16
broadcast(SSID)	☒ Enable ☐ Disable
AP Isolation	☐ Enable ☒ Disable
MBSSID AP Isolation	☐ Enable ☒ Disable
BSSID	00:21:F2:10:CC:1C
Frequency (Channel)	Auto ▼
HT Physical Mode	
Operating Mode	☒ Mixed Mode ☐ Green Field
Channel BandWidth	☐ 20 ☒ 20/40
Guard Interval	☐ Long ☒ Short
Reverse Direction Grant(RDG)	☒ Disable ☐ Enable
STBC	☐ Disable ☒ Enable
Aggregation MSDU(A-MSDU)	☒ Disable ☐ Enable
Auto Block ACK	☐ Disable ☒ Enable
Decline BA Request	☒ Disable ☐ Enable
HT Disallow TKIP	☐ Disable ☒ Enable
HT LDPC	☒ Disable ☐ Enable

Field Name	Description
Radio on/off	Select “Radio off” to disable wireless. Select “Radio on” to enable wireless.
Wireless connection	According to the wireless client type, select one of these modes.
Network Mode	Choose one network mode from the drop down list. Default is 11b/g/n mixed mode



SSID	It is the basic identity of wireless LAN. SSID can be any alphanumeric or a combination of special characters. It will appear in the wireless network access list.
Multiple SSID1~SSID3	The device supports 4 SSIDs.
Hidden	After the item is checked, the SSID is no longer displayed in the search for the Wi-Fi wireless network connection list
Broadcast(SSID)	After initial State opening, the device broadcasts the SSID of the router to wireless network
AP Isolation	If AP isolation is enabled, the clients of the AP cannot access each other
MBSSID AP Isolation	AP isolation among the devices which are not belong to this AP and along to, when the option is enabled, the devices which do not belong to this AP cannot access the devices which are within the AP.
BSSID	A group of wireless stations and a WLAN access point (AP) consists of a basic access device (BSS), each computer in the BSS must be configured with the same BSSID, that is, the wireless AP logo
Frequency (Channel)	You can select Auto Select and channel 1/2/3/4/5/6/7/8/9/10/11.
HT Physical Mode Operating Mode	Mixed Mode: In this mode, the previous wireless card can recognize and connect to the Pre-N AP, but the throughput will be affected Green Field: high throughput can be achieved, but it will affect backward compatibility, and security of the system
Channel Bandwidth	Select channel bandwidth, default is 20 MHz and 20/40 MHz.
Guard Interval	The default is automatic, in order to achieve good BER performance, you must set the appropriate guard interval
Reverse Dirction Grant (RDG)	Enabled: Devices on the WLAN are able to transmit to each other without requiring an additional contention-based request to transfer (i.e. devices are able to transmit to another device on the network during TXOP) Disabled: Devices on the WLAN must make a request for transmit when
STBC	Space-time Block Code

	Enabled: Multiple copies of signals are transmitted to increase the chance of successful delivery
Aggregation MSDU (A-MSDU)	Enabled: Allows the device to aggregate multiple Ethernet frames into a single 802.11n, thereby improving the ratio of frame data to frame overhead
Auto Block Ack	Enabled: Multiple frames are acknowledged together using a single Block Acknowledgement frame. Disabled: Auto block acknowledgement is not used by the device – use this configuration when low throughput/connectivity issues are
Decline BA Request	Enabled: Disallow block acknowledgement requests from devices Disabled: Allow block acknowledgement requests from devices
HT Disallow TKIP	Enabled: Disallow the use of Temporal Key Integrity Protocol for connected devices Disabled: Allow the use of Temporal Key Integrity Protocol for connected devices
HT LDPC	Enabled: Enable Low-Density Parity Check mechanism for increasing chance of successful delivery in challenging wireless environments Disabled: Disable Low-Density Parity Check mechanism

Wireless Security

Table 23 Wireless security

Status	Network	Wireless	SIP Account	Phone	Administration
Basic	Wireless Security	WMM	WDS	WPS	Station Info
Advanced					

WIFI Security Setting

Select SSID

SSID choice

FTA1101-10CC1C ▼

"FTA1101-10CC1C"

Security Mode

WPA-PSK ▼

WPA

WPA Algorithms

☐ TKIP
 ☒ AES
 ☐ TKIPAES

Pass Phrase

Key Renewal Interval

3600 sec (0 ~ 86400)

Access policy

Policy

Disable ▼

Add a station MAC

(The maximum rule count is 64)

Field Name	Description
SSID Choice	Choose one SSID from SSID, Multiple SSID1, Multiple SSID2 and Multiple
Security Mode	Select an appropriate encryption mode to improve the security and privacy of your wireless data packets.Each encryption mode will bring out different web page and ask you to offer additional configuration.

User can configure the corresponding parameters. Here are some common encryption methods:

OPENWEP: A handshake way of WEP encryption, encryption via the WEP key:

Table 24 WiFi Security Setting

WIFI Security Setting					
Select SSID					
SSID choice		FTA1101-10CC1C ▼			
"FTA1101-10CC1C"		Security Mode			
		OPENWEP ▼			
Wire Equivalence Protection (WEP)		Default Key			
		WEP Key 1		WEP Key 1 ▼	
		*****		Hex ▼	64bit ▼
WEP Keys		WEP Key 2		*****	
		WEP Key 3		*****	
		WEP Key 4		*****	
		WEP Key 1		Hex ▼	64bit ▼
		WEP Key 2		Hex ▼	64bit ▼
		WEP Key 3		Hex ▼	64bit ▼
		WEP Key 4		Hex ▼	64bit ▼

Field Name	Description
------------	-------------

Security Mode	This is used to select one of the 4 WEP keys, key settings on the clients should be the same with this when connecting.
WEP Keys	Set the WEP key. A-64 key need 10 Hex characters or 5 ASCII characters; choose A-128 key need 26 Hex characters or 13 ASCII characters.
WEP represents Wired Equivalent Privacy, which is a basic encryption method.	

WPA-PSK, the router will use WPA way which is based on the shared key-based .

Table 25 WPA-PSK

WIFI Security Setting

Select SSID

SSID choice FTA1101-10CC1C ▼

"FTA1101-10CC1C"

Security Mode WPA-PSK ▼

WPA

WPA Algorithms ☐ TKIP ☒ AES ☐ TKIPAES

Pass Phrase *****

Key Renewal Interval 3600 sec (0 ~ 86400)

Field Name	Description
WPA Algorithms	This item is used to select the encryption of wireless home gateway algorithms, options are TKIP, AES and TKIPAES.
Pass Phrase	Setting up WPA-PSK security password.
Key Renewal Interval	Set the key scheduled update cycle, default is 3600s.

WPAPSKWPA2PSK manner is consistent with WPA2PSK settings:

Table 26 WPAPSKWPA2PSK

WIFI Security Setting

Select SSID

SSID choice FTA1101-10CC1C ▼

"FTA1101-10CC1C"

Security Mode WPAPSKWPA2PSK ▼

WPA

WPA Algorithms ☐ TKIP ☒ AES ☐ TKIPAES

Pass Phrase *****


Key Renewal Interval 3600 sec (0 ~ 86400)

Field Name	Description
WPA Algorithms	The home gateway is used to select the wireless security encryption algorithm options are TKIP, AES, TKIP / AES. 11N mode does not
Pass Phrase	Set WPA-PSK/WPA2-PSK security code
Key Renewal Interval	Set the key scheduled update cycle, default is 3600s

WPA-PSK/WPA2-PSK WPA/WPA2 security type is actually a simplified version, which is based on the WPA shared key mode, higher security setting is also relatively simple, suitable for ordinary home users and small businesses.

Wireless Access Policy

Table 27 Wireless Access Policy

	
Field Name	Description
Access policy	Wireless access control is used to allow or prohibit the specified client to access to your wireless network based on the MAC address.
Policy	Disable : Prohibition: wireless access control policy. Allow: only allow the clients in the list to access. Rejected: block the clients in the list to access.
Add a station MAC	Enter the MAC address of the clients which you want to allow or prohibit Example: Prohibit the device whose wireless network card MAC address is 00:1F: D0: 62: BA:FF's to access the wireless network, and allow other computers to access the network.Implementation: As shown, the Policy is Reject, add 00:1F: D0: 62: BA: FF to the MAC, click Save and reboot the device settings to take effect.

Wi-Fi Repeater

Connects to an upstream Wi-Fi network and extends wireless coverage.

Navigation:

1. Navigate to Wireless--Basic on the web page
2. Change "Wireless Connection Mode" to "Repeater"

VoIP ... control panel Current Time: Admin Mode

Wireless | SIP Account | Phone | Administration

Basic | Wireless Security | WMM | WDS | WPS | Station Info | Advanced

Basic Wireless Settings

Radio On/Off: Radio On ▾

Wireless Connection Mode: Repeater ▾

Network Mode: 11b/g/n mixed mode ▾

Multiple SSID: FTA1101-61DB0F Enable ☒ Hidden ☐ Isolated ☐ Max Client: 16

Field Name	Description
Wireless Connection Mode	According to the wireless client type, select one of these modes. Select "AP" to to work as a wireless access point. Select "Repeater" to extend an existing Wi-Fi network while also providing wireless access.
SSID	It is the basic identity of wireless LAN. SSID can be any alphanumeric or a combination of special characters. It will appear in the wireless network access list.

3. Navigate to "Wireless"-->"Repeater" page, FTA1101 will scan and display AP information here.

Wireless | SIP Account | Phone | Administration

Basic | Wireless Security | WMM | WDS | WPS | Station Info | Advanced | Repeater

Please REBOOT to make the changes effective!

Wireless Connection

Wireless Connection

Connection Status: Disconnected

SSID	BSSID	Authentication	Encryption	Status
FR3000_2.4G	00:21:f2:51:8e:80	OPEN	NONE	
5120SAS-方案墙Wi-Fi	00:21:f2:3c:e7:f4	OPEN	NONE	
QX3646680	00:21:f2:64:66:80	WPA1PSK/WPA2PSK	TKIP/AES	
hw_manage_fit_6520	78:5c:5e:36:65:2b	OPEN	NONE	
ChinaNet-eK4J	9a:00:74:32:9c:eb	WPA2PSK	TKIP/AES	
Flyingvoice	44:00:4d:18:74:c0	WPA1PSK/WPA2PSK	AES	


Field Name	Description
Connection Status	Indicates whether the device is currently connected or disconnected from the network.
SSID	The name of the wireless network.
BSSID	The MAC address of the connected access point.
Authentication	The security authentication method used for the Wi-Fi connection.
Encryption	The encryption type used to secure the wireless communication.
Status	Shows the current working state of the connection or interface.

4. Choose one SSID, and scroll to bottom of the page




Field Name	Description
Connect	Initiates a connection to the selected network or device.
Refresh	Reloads the current list or updates the latest status information.
Add	Adds a new Wi-Fi network profile for connection.

5. Enter password



6. Check connection on the top of page



Status **Network** **Wireless** **SIP Account** **Phone** **Administration**

Basic Wireless Security WMM WDS WPS Station Info Advanced Repeater

Please REBOOT to make the changes effective!


Wireless Connection

Wireless Connection

Connection Status Connected (AP: Flyingvoice; BSSID: 44:00:4D:18:74:C0)

SSID	BSSID	Authentication	Encryption	Status
Flyingvoice	44:00:4d:18:74:c0	WPA1PSK/WPA2PSK	AES	

7. Reboot FTA1101 to apply new change



8. After reboot, check Wi-Fi connection on Status page (Connected AP"Flyingvoice")

Network Status	
Ethernet WAN Port Status	
WAN Port Status	Link Down
Wi-Fi Port Status	Connected (AP: Flyingvoice)
Connection Type	DHCP
IP Address	192.168.10.170
Subnet Mask	255.255.255.0
Default Gateway	192.168.10.1
Primary DNS	8.8.8.8
Secondary DNS	114.114.114.114
WAN Down Speed	0B/s
WAN Upload Speed	0B/s

WMM

Table 28 WMM

BasicWireless SecurityWMMWDSWPSStation InfoAdvanced

WMM Parameters of Access Point

	AIFSN	CWMin	CWMax	TXOP	ACM	AckPolicy
AC_BE	3	15 ▾	63 ▾	0	☐	☐
AC_BK	7	15 ▾	1023 ▾	0	☐	☐
AC_VI	1	7 ▾	15 ▾	94	☐	☐
AC_VO	1	3 ▾	7 ▾	47	☐	☐

Save & ApplyApplyCancel

Description

WMM (Wi-Fi Multi-Media) is the QoS certificate of Wi-Fi Alliance (WFA). This provides you to configure the parameters of wireless multimedia; WMM allows wireless communication to define a priority according to the home gateway type. To make WMM effective, the wireless clients must also support WMM.

WDS

Table 29 WDS

BasicWireless SecurityWMMWDSWPSStation InfoAdvanced

WDS Setting

WDS Config

WDS Mode

Disable
Disable
Lazy Mode
Bridge Mode
Repeater Mode

Save & ApplySave

Description

WDS stands for Wireless Distribution System, enabling WDS access points to be interconnected to expand a wireless network.

Station Info

Table 30 Station info

StatusNetworkWireless 2.4GHzWireless 5GHzSIPFXS1FXS2SecurityApplication

BasicWireless SecurityWMMWDSWPSStation InfoAdvanced

Wireless Status

Wireless Status

Current ChannelChannel 1

FWR9502-0000C800:21:F2:00:00:10

Wireless Network

Wireless Network

MAC AddressAidPSMMIMO PS

TX RateTxBRSSIStream SNRSnd Rsp SNRLast RX RateConnect Time

Description


This page displays information about the current registered clients' connections including operating MAC address and operating statistics.

Advanced

52

Table 31 Advanced

Basic	Wireless Security	WMM	WDS	WPS	Station Info	Advanced
Advanced Wireless						
Advanced Wireless						
BG Protection Mode	Auto ▼					
Beacon Interval	100 ms (range 20 - 999, default 100)					
Data Beacon Rate (DTIM)	3 (range 1 - 255, default 3)					
Fragment Threshold	2346 (range 256 - 2346, default 2346)					
RTS Threshold	2347 (range 1 - 2347, default 2347)					
TX Power	100 % (range 1 - 100, default 100)					
Short Preamble	☒ Enable ☐ Disable					
Short Slot	☒ Enable ☐ Disable					
TX Burst	☒ Enable ☐ Disable					
Pkt_Aggregate	☒ Enable ☐ Disable					
Country Code	NONE ▼					
Support Channel	Ch1~14 ▼					
Tx Beamforming	Disable ▼					
Wi-Fi Multimedia						
WMM Capable						
Multiple SSID	☒					
Multiple SSID1	☐					
Multiple SSID2	☐					
Multiple SSID3	☐					
APSD Capable	☐ Enable ☒ Disable					
Multicast-to-Unicast Converter						
Multicast-to-Unicast	☐ Enable ☒ Disable					
Field Name		Description				
BG Protection		Select G protection mode, options are on, off and automatic.				
Beacon Interval		The interval of sending a wireless beacon frame, within this range, it will send a beacon frame for the information of the surrounding radio network.				
Data Beacon Rate(DTIM)		Specify the interval of transmitting the indication message, it is a kind of cut down operation, and it is used for informing the next client which is going to receive broadcast multi-cast.				
Fragment Threshold		Specify the fragment threshold for the packet, when the length of the packet exceeds this value, the packet is divided.				

RTS Threshold	Specify the packet RTS threshold, when the packet exceeds this value, the router will send RTS to the destination site consultation
TX Power	Define the transmission power of the current AP, the greater it is, the stronger the signal is
Short Preamble	Choose enable or disable
Short Slot	Enable/Disable short slot. By default it is enabled, it is helpful in improving the transmission rate of wireless communication
Tx Burst	One of the features of MAC layer, it is used to improve the fairness for transmitting TCP
Pkt_Aggregate	It is a mechanism that is used to enhance the LAN, in order to ensure that the home gateway packets are sent to the destination correctly
Support Channel	Choose appropriate channel
Wi-Fi Multimedia (WMM)	
WMM Capable	Enable/Disable WMM.
APSD Capable	Enable/Disable APSD. Once it is enabled, it may affect wireless performance, but can play a role in energy-saving power
WMM Parameters	Press  , the webpage will jump to the configuration page of Wi-Fi multimedia
Multicast-to-Unicast Converter	Enable/Disable Multicast-to-Unicast. By default, it is Disabled

SIP Account

SIP Account

Basic

Set the basic information provided by your VOIP Service Provider, such as Phone Number, Account, password, SIP Proxy and others.

Table 32 Line

Status	Network	Wireless	SIP Account	Phone	Administration
Line 1	SIP Settings	VoIP QoS			

Basic			
Basic Setup			
Line Enable	Enable ▼	Outgoing Call without Registration	Disable ▼
Proxy and Registration			
Proxy Server	199.193.188.184	Proxy Port	5060
Outbound Server		Outbound Port	5060
Backup Outbound Server		Backup Outbound Port	5060
Allow DHCP Option 120 to Override SIP Server	Disable ▼		
Subscriber Information			
Display Name	8674485916	Phone Number	8674485916
Account	8674485916	Password	

Field Name	Description
Line Enable	Enable/Disable the line.
Outgoing Call without Registration	Enable/Disable Outgoing Call without Registration If enabled, SIP-1 will not send register request to SIP server; but in Status/ SIP Account Status webpage, Status is Registered; lines 1 can dial out, but the external line number cannot dialed line1.
Proxy Server	The IP address or the domain of SIP Server
Outbound Server	The IP address or the domain of Outbound Server
Backup Outbound	The IP address or the domain of Backup Outbound Server
Proxy port	SIP Service port, default is 5060
Outbound Port	Outbound Proxy's Service port, default is 5060
Backup Outbound Port	Backup Outbound Proxy's Service port, default is 5060

Display Name	The number will be displayed on LCD
Phone Number	Enter telephone number provided by SIP Proxy
Account	Enter SIP account provided by SIP Proxy
Password	Enter SIP password provided by SIP Proxy

Audio Configuration

Table 33 Audio configuration

Audio Configuration			
Codec Setup			
Audio Codec Type 1	G.711U ▼	Audio Codec Type 2	G.711A ▼
Audio Codec Type 3	G.729 ▼	Audio Codec Type 4	G.722 ▼
Audio Codec Type 5	G.723 ▼	Audio Codec Type 6	G726-32 ▼
Audio Codec Type 7	iLBC ▼		
G.723 Coding Speed	5.3k bps ▼	Packet Cycle (ms)	20 ▼
Silence Supp	Disable ▼	Echo Cancel	Enable ▼
Auto Gain Control	Disable ▼	Use First Matching Vocoder in 2000K SDP	Disable ▼
Codec Priority	Remote ▼	Packet Cycle Follows Remote SDP	Disable ▼
FAX Configuration			
FAX Mode	T.30 ▼	Bypass Attribute Value	fax/modem ▼
Enable T.38 CNG Detect	Disable ▼	Enable T.38 CED Detect	Enable ▼
Enable gpmid attribute	Disable ▼	T.38 Redundancy	Disable ▼
Max Fax Rate	14400 ▼		

Field Name	Description
Audio Codec Type1	Choose the audio codec type from G.711U, G.711A, G.722, G.729,
Audio Codec Type2	Choose the audio codec type from G.711U, G.711A, G.722, G.729,
Audio Codec Type3	Choose the audio codec type from G.711U, G.711A, G.722, G.729,
Audio Codec Type4	Choose the audio codec type from G.711U, G.711A, G.722, G.729,
Audio Codec Type5	Choose the audio codec type from G.711U, G.711A, G.722, G.729,
G.723 Coding Speed	Choose the speed of G.723 from 5.3kbps and 6.3kbps
Packet Cycle	The RTP packet cycle time, default is 20ms
Silence Supp	Enable/Disable silence support
Echo Cancel	Enable/Disable echo cancel. By default, it is enabled
Auto Gain Control	Enable/Disable auto gain
T.38 Enable	Enable/Disable T.38

T.38 Redundancy	Enable/Disable T.38 Redundancy
T.38 CNG Detect	Enable/Disable T.38 CNG Detect
gpmd attribute Enable	Enable/Disable gpmd attribute

Supplementary Service Subscription

Table 34 Supplementary service

Supplementary Service Subscription

Supplementary Services

Call Waiting

Enable ▾

Hot Line

Enable MWI

Enable ▾

Voice Mailbox Numbers

MWI Subscribe Enable

Disable ▾

VMWI Serv

Enable ▾

Disable MWI Tone

Disable ▾

DND

Disable ▾

Outgoing Call Block Password

....

Outgoing Call Active Password

....

Speed Dial

Speed Dial 2

Speed Dial 3

Speed Dial 4

Speed Dial 5

Speed Dial 6

Speed Dial 7

Speed Dial 8

Speed Dial 9

Field Name	Description
Call Waiting	Enable/Disable Call Waiting
Hot Line	Fill in the hotline number,Pickup handset or press hands-free or headset button, the device will dial out the hotline number automatically
MWI Enable	Enable/Disable MWI (message waiting indicate). If the user needs to user voice mail, please enable this feature
MWI Subscribe	Enable/Disable MWI Subscribe
Voice Mailbox Numbers	Fill in the voice mailbox phone number, Asterisk platform, for example, its default voice mail is *97
VMWI Serv	Enable/Disable VMWI service
DND	Enable/Disable DND (do not disturb)
Speed Dial	Enter the speed dial phone numbers. Dial *74 to active speed dial function Then press the speed dial numbers, for example, press 2, phone dials 075526099365 directly

Advanced

Table35 Advanced

Advanced			
SIP Advanced Setup			
Domain Name Type	Enable ▼	Carry Port Information	Disable ▼
Signal Port	54180	DTMF Type	RFC2833 ▼
RFC2833 Payload (>=96)	101	Register Refresh Interval (sec)	3600
Caller ID Header	FROM ▼	Remove Last Reg	Enable ▼
Session Refresh Time (sec)	0	Refresher	UAC ▼
Enable SIP 100REL	Enable ▼	Enable SIP OPTIONS	Disable ▼
Initial Reg With Authorization	Disable ▼	Reply 182 On Call Waiting	Disable ▼
Primary Server Detect Interval	0	Max Detect Fail Count	3
NAT Keep-alive Interval (10-60s)	15	Anonymous Call	Disable ▼
Anonymous Call Block	Disable ▼	Proxy DNS Type	A Type ▼
Use OB Proxy in Dialog	Disable ▼	Complete Register	Disable ▼
Enable Reg Subscribe	Disable ▼	Reg Subscribe Interval (sec)	0
Dial Prefix		User Type	IP ▼
Hold Method	ReINVITE ▼	Request-URI User Check	Disable ▼
Only Recv Request From Server	Disable ▼	Server Address	
SIP Received Detection	Disable ▼	VPN	Disable ▼
SIP Encrypt Type	Disable ▼	RTP Encrypt Type	Disable ▼
Country Code		Remove Country Code	Disable ▼
Tel URL	Disable ▼	Use Random SIP Port	Enable ▼
Min Random SIP Port	50000	Max Random SIP Port	60000
Prefer Primary SIP Server	Disable ▼	Hold SDP Attribute Inactive	Disable ▼
Remove All Bindings	Disable ▼	VAD&CNG	Disable ▼
RTP Advanced Setup			
RTP Port Min	0 (0 means auto select)	RTP Port Max	50000

Parameter name	Description
Domain Name Type	Whether to enable domain name recognition in SIP URIs
Carry Port Information	Whether to carry the SIP URI port information
Signal Port	The local port number of the SIP protocol
DTMF Type	Select the second way of dialing, optional items are In-band, RFC2833 and SIP Info.
RFC2833 Payload(>=96)	The user can use the default settings
Register Refresh Interval(sec)	The time interval between two normal registration messages. The user can use the default settings.
Caller ID Header	When enabled, an unregistered message will be sent before the registration is disabled, and no unregistered messages will be sent before registration; should be set according to the different server requirements

Remove Last Reg	Whether to remove the last registration message
Session Refresh Time(sec)	The interval between two sessions, the user can use the default settings
Refresher	Select Refresh from UAC and UAS
SIP 100REL Enable	If this option is enabled, the IP phone will send SIP-OPTION to the server instead of sending Hello messages on a regular basis. The interval for sending is the parameter set for the "NAT Hold Interval" parameter.
SIP OPTIONS Enable	Whether to open the SIP OPTION function
Initial Reg With Authorization	Whether to carry the certification information when registering
Reply 182 On Call Waiting	Whether or not to send 182 when the call is waiting
NAT Keep-alive Interval(10-60s)	The time interval for sending empty packets
Anonymous Call	Whether anonymous calls are enabled
Anonymous Call Block	Whether to enable anonymous call blocking
Proxy DNS Type	Set the DNS server type, the optional items are Type A, DNS SRV, and Auto
Use OB Proxy In Dialog	Whether the OB agent is used in the conversation
Complete Register	Whether to enable full registration
Reg Subscribe Enable	When enabled, the subscription message is sent after the registration message; the subscription message is not sent when disabled
Reg Subscribe Interval(sec)	Enable or disable the Reg Subscribe Interval
Dial Prefix	Dial before prefix
User Type	Whether the end user is IP or Phone
Hold Method	Call hold is REINVITE or INFO
Request-URI User Check	Whether to allow the user to check
Only Recv Request From Server	If enabled, will only accept requests from the server, do not accept other requests
Server Address	SIP server address
SIP Received Detection	Whether to allow SIP receive detection
VPN	Whether to enable VPN
SIP Encrypt Type	Whether to allow SIP message encryption
RTP Encrypt Type	Whether to allow RTP message encryption
Country Code	Country code
Remove Country Code	Whether to allow the removal of national codes

Tel URL	Whether to open the Tel URL
Use Random SIP Port	Whether to use the minimum random port
Min Random SIP Port	SIP minimum random port
Max Random SIP Port	SIP maximum random port
Prefer Primary SIP Server	Whether to enable the preferred primary server
Hold SDP Attribute Inactive	Whether to enable the call to keep the inactive attribute
RTP Port Min	RTP minimum port
RTP Port Max	RTP's maximum port

SIP Settings

Table 36 SIP Settings

Status	Network	Wireless	SIP Account	Phone	Administration
Line 1	SIP Settings	VoIP QoS			

SIP Parameters

SIP Parameters

SIP T1	500	ms	Max Forward	70
SIP User Agent Name	FLYINGVOICE		Max Auth	2
Reg Retry Intvl	30	sec	Reg Retry Long Intvl	1200
Mark All AVT Packets	Enable		RFC 2543 Call Hold	Enable
SRTP	Disable		SRTP Prefer Encryption	AES_CM
Service Type	Common		DNS Refresh Timer	0
				sec

Response Status Code Handling

Retry Reg RSC	
---------------	--

NAT Traversal

NAT Traversal

NAT Traversal	STUN	STUN Server Address	83.211.9.232
NAT Refresh Interval (sec)	60	STUN Server Port	3478

Parameters name	Description
SIP Parameters	
SIP T1	The default value is 500
SIP User Agent Name	Enter the SIP User Agent header field
Max Forward	Modify the maximum hop value, the default is 70

Max Auth	Change the number of authentication failures, the default value is 2
Reg Retry Intvl	Registration failed again registration interval, default is 30
Reg Retry Long Intvl	Registration failed Register again for the long interval Default 1200
Mark All AVT Packets	The default enable is on
RFC 2543 Call Hold	The default enable is on
SRTP	The default is disabled
SRTP Prefer Encryption	Support for AES_CM and ARIA_CM
Service Type	Default general
DNS Refresh Timer	Modify the DNS refresh time, the default value of 0
Transport	The transmission type defaults to UDP
NAT Traversal	
NAT Traversal	Whether to enable NAT mode, or select STUN to penetrate
STUN Server Address	STUN server IP address
NAT Refresh Interval(sec)	Refresh interval
STUN Server Port	STUN port, the default is 3478

VoIP QoS

Table 37 VoIP QoS

Status	Network	SIP	FXS1	FXS2	Administration
SIP Settings	VoIP QoS	Dial Rule	Blacklist	Call Log	
QoS Settings					
Layer 3 QoS					
SIP QoS(0-63)		46			
RTP QoS(0-63)		46			
Parameters name		Description			
SIP QoS(0-63)		Defaults to 46,you can set a range of values is 0~63			
RTP QoS(0-63)		Defaults to 46,you can set a range of values is 0~63			

Phone

Preferences

Preferences

SIP Account		Preferences	
Preferences			
Volume Settings			
Handset Input Gain	5 ▼	Handset Volume	5 ▼
DTMF Volume (0~-45)	-19		

Field Name	Description
Handset Input Gain	Adjust the handset input gain from 0 to 7.
Handset Volume	Adjust the output gain from 0 to 7.
DTMF Volume (0~-	Default is -19, you can set a range of values is 0~ -45

Regional

Table 38 Regional

Regional			
Tone Type	China ▼		
Dial Tone			
Busy Tone			
Off-hook Warning Tone			
Ring Back Tone			
Call Waiting Tone			
Ringing Tone			
Min Jitter Delay (0-600ms)	20	Max Jitter Delay (20-1000ms)	160
Ringing Time (10-300sec)	60		
Ring Waveform	Sinusoid ▼	Ring Voltage (40-63 Vrms)	45
Ring Frequency (15-30Hz)	25	VMWI Ring Splash Len (0.1-10sec)	0.5
Flash Time Max (0.2-1sec)	0.9	Flash Time Min (0.1-0.5sec)	0.1

Dial Tone	Dial Tone
Busy Tone	Busy Tone

Off Hook Warning	Off Hook warning tone
Ring Back Tone	Ring back tone
Call Waiting Tone	Call waiting tone
Min Jitter Delay	The Min value of home gateway's jitter delay, home gateway is an adaptive jitter mechanism.
Max Jitter Delay	The Max value of home gateway's jitter delay, home gateway is an adaptive jitter mechanism.
Ringing Time	How long FTA1101 will ring when there is an incoming call.
Ring Waveform	Select regional ring waveform, options are Sinusoid and Trapezoid, the default Sinusoid.
Ring Voltage	Set ringing voltage, the default value is 70
Ring Frequency	Set ring frequency, the default value is 25
VMWI Ring Splash Len(sec)	Set the VMWI ring splash length, default is 0.5s.
Flash Time Max(sec)	Set the Max value of the device's flash time, the default value is 0.9
Flash Time Min(sec)	Set the Min value of the device's flash time, the default value is 0.1

Features and Call Forward

Table 39 Features and call forward

Features			
All Forward	Disable ▼	Busy Forward	Disable ▼
No Answer Forward	Disable ▼	Transfer On-hook	Enable ▼
Call Forward			
All Forward		Busy Forward	
No Answer Forward		No Answer Timeout	20
Feature Code			
Hold Key Code	*77	Conference Key Code	*88
Transfer Key Code	*98	IVR Key Code	****
Enable R Key	Disable ▼	R Key Cancel Code	R1 ▼
R Key Hold Code	R2 ▼	R Key Transfer Code	R4 ▼
R Key Conference Code	R3 ▼	Speed Dial Code	*74
Cfwd All Act Code	*72	Cfwd All Deact Code	*73
Cfwd Busy Act Code	*90	Cfwd Busy Deact Code	*91
Cfwd No Ans Act Code	*52	Cfwd No Ans Deact Code	*53
DND Act Code	*78	DND Deact Code	*79

Field Name		Description
Features	All Forward	Enable/Disable forward all calls
	Busy Forward	Enable/Disable busy forward.
	No Answer Forward	Enable/Disable no answer forward.
Call Forward	All Forward	Set the target phone number for all forward.
		The device will forward all calls to the phone number immediately when there is an incoming call.
	Busy Forward	The phone number which the calls will be forwarded to when line is busy.
	No Answer Forward	The phone number which the call will be forwarded to when there's no answer.
	No Answer Timeout	The seconds to delay forwarding calls, if there is no answer at your phone.
Feature Code	Hold key code	Call hold signatures, default is *77.
	Conference key	Signature of the tripartite session, default is *88.
	Transfer key code	Call forwarding signatures, default is *98.
	IVR key code	Signatures of the voice menu, default is ****.
	R key enable	Enable/Disable R key way call features.
	R key cancel code	Set the R key cancel code, option are ranged from R1 to R9, default value is R1.
	R key hold code	Set the R key hold code, options are ranged from R1 to R9, default value is R2.
	R key transfer code	Set the R key transfer code, options are ranged from R1 to R9, default value is R4.
	R key conference code	Set the R key conference code, options are ranged from R1 to R9, default value is R3.
	R Key Reject 2nd Call Code	Set the R key Reject 2nd Call code, options are ranged from R1 to R9, default value is R0.
	Speed Dial Code	Speed dial code, default is *74.

Miscellaneous

Table 40 Miscellaneous

Miscellaneous

Loop Current	26	Impedance Matching	US PBX,Korea,Taiwan(600)
CID Service	Enable	CWCID Service	Disable
Caller ID Method	Bellcore	Polarity Reversal	Disable
Dial Time Out (IDT)	5	Call Immediately Key	#
ICMP Ping	Disable	Enable Escaped Char	Disable
Bellcore Style 3-Way Conference	Disable	On-hook Voltage	48

Field Name	Description
Codec Loop	Set off-hook loop current, default is 26
Impedance	Set impedance matching, default is US PBX,Korea,Taiwan(600).
CID service	Enable/Disable displaying caller ID; If enable, caller ID is displayed when there is an incoming call or it won't be displayed. Default is enable.
CWCID Service	Enable/Disable CWCID. If enable, the device will display the waiting call's caller ID, or it won't display. Default is disable.
Dial Time Out	How long device will sound dial out tone when device dials a number.
Call Immediately	Choose call immediately key form * or #.
ICMP Ping	Enable/Disable ICMP Ping. If enable this option, home gateway will ping the SIP Server every interval time, otherwise, It will send "hello" empty packet to the SIP Server.
Escaped char enable	Open special character translation function; if enable, when you press the # key, it will be translated to 23%, when disable, it is just #

Dial Rule

Table 41 Dial Plan

Status	Network	Wireless	SIP Account	Phone	Administration
Preferences	Dial Rule	Phone Book	Call Log		

Dial Rule

General

Dial Rule: Enable ▾
Unmatched Policy: Accept ▾

No.	Line	Digit Map	Action	Move Up	Move Down	
1	Line1	WD	Deny	⬆	⬇	⊞

Line: Line1 ▾
Digit Map:
Action: Deny ▾
OK Cancel

Field Name	Description
Dial Plan	Enable/Disable dial plan.
Line	Set the line.
Digit Map	Enter the sequence used to match input number The syntactic, please refer to the following Dial Plan Syntactic.
Action	Choose the dial plan mode from Deny and Dial Out. Deny means router will reject the matched number, while Dial Out means router will dial out the matched number.
Move Up	Move the dial plan up the list.
Move Down	Move the dial plan down the list.

Adding one Dial Plan

Table 42 Adding one dial plan

Dial Plan

General

Dial Plan

Disable

Unmatched Policy

No.

FXS

Digit Map

Action

Move Up

Move Down

FXS

FXS 1

Digit Map

Action

Deny

OK

Cancel

Description

Step 1. Enable Dial Plan.

Step 2. Click Add button, and the configuration table.

Step 3. Fill in the value of parameters.

Step 4. Press OK button to end configuration.

Dial Plan Syntactic

Table 43 Dial Plan Syntactic

No.	String	Description
1	0 1 2 3 4 5 6 7 8 9 * #	Allowed characters
2	x	Lowercase letter x stands for one legal character
3	[sequence]	To match one character form sequence. For example: [0-9]: match one digit form 0 to 9 [23-5*]: match one character from 2 or 3 or 4 or 5 or * x ⁰ x ¹ x ² x ³ x ⁿ
4	x.	Match to , , , For example: “01.” :can match ” 0” , “01” , “011” , “0111” , ,” 01111...”
5	<diald:substituted>	Replace diald with substituted. For example: <8:1650>123456: input is “85551212” , output is “16505551212”

		Make outside dial tone after dialing “x” , stop until dialing character “y” For example:
6	x,y	“9,1xxxxxxxxxx” :the device reports dial tone after inputting “9” , stops tone until inputting “1” “9,8,010x” : make outside dial tone after inputting “9” , stop tone until inputting “0”
7	T	Set the delayed time. For example: “<9:111>T2” : The device will dial out the matched number “111” after 2 seconds.

Blacklist

In this page, user can upload or download Phonebook/blacklist file, or add or delete or edit blacklist one by one.

Upload or download Phonebook/blacklist file

Table 44 Blacklist

Status	Network	SIP	FXS1	FXS2	Administration
SIP Settings	VoIP QoS	Dial Rule	Blacklist	Call Log	

Phone Book Upload & Download

Phone Book Upload & Download

Local File 选择文件 未选择任何文件
Upload XML Download XML

Blacklist Upload & Download

Blacklist Upload & Download

Local File 选择文件 未选择任何文件
Upload CSV Download CSV

Steps:

1. Click 选择文件 ,select a locally stored phonebook.
2. There will be a tips after select successfully.

Phone Book Upload & Download

Local File 选择文件 Phonebook.csv
Upload XML Download XML

3. Click Upload XML , begin upload.
4. Click Download XML ,begin download

Call Log

To view the call log information such as redial list , answered call and missed call

Table 45 Call log

Redial Calls				
Redial List				
Index	NUMBER	Start Time	Duration	☐
1	123	10/28 10:30	00:00:07	☐
2	010123	10/28 12:02	00:00:01	☐
3	010123	10/28 16:16	00:00:00	☐
4	010123	10/28 16:16	00:00:00	☐
5	123	10/28 16:20	00:00:13	☐
6	123	10/28 16:21	00:00:34	☐
7	123	10/29 10:50	00:00:10	☐
8	123	10/29 14:36	00:00:01	☐
9	123	10/29 15:05	00:00:23	☐
10	123	10/29 15:06	00:00:05	☐
11	123	10/29 15:07	00:00:01	☐
Answered Calls				
Answered Calls				
Index	NUMBER	Start Time	Duration	☐
1	22222	10/21 09:56	00:00:40	☐
2	110	10/21 18:14	00:00:03	☐
3	110	10/21 18:15	00:00:07	☐
4	sipp	10/23 13:40	00:00:06	☐
5	sipp	10/24 18:05	00:00:05	☐
6	sipp	10/24 18:05	00:00:05	☐
7	sipp	10/25 15:38	00:00:03	☐
8	sipp	10/25 15:42	00:00:06	☐
9	sipp	10/25 15:55	00:00:10	☐
10	sipp	10/25 16:03	00:00:02	☐
11	sipp	10/25 16:15	00:00:02	☐
Missed Calls				
Missed Calls				
Index	NUMBER	Start Time	Duration	☐
1	110	10/21 09:50	00:00:03	☐
2	555	10/22 12:04	00:00:03	☐

Administration

The user can manage the device in these webpages; you can configure the Time/Date, password, web access, system log and associated configuration TR069.

Management

Save config file

Table 46 Save Config File

Save Config File Config File Upload & Download Local File 选择文件 未选择任何文件 UploadDownload	
Field Name	Description
Config file upload and download	Upload: click on browse, select file in the local, press the upload button to begin uploading files
	Download: click to download, and then select contains the path to download the configuration file

Administrator settings

Table 47 Administrator settings

Administrator Settings	
Password Reset	
User Type	Admin User ▼
New User Name	admin
New Password	(The maximum length is 25)
Confirm Password	
Language	
Language	English ▼
VPN Access	
Management Using VPN	Disable ▼
Web Access	
Remote Web Login	Enable ▼
Web Port	80
Web SSL Port	443
Web Idle Timeout (0 - 60min)	5
Allowed Remote IP (IP1;IP2;...)	0.0.0.0
Telnet Access	
Remote Telnet	Enable ▼
Telnet Port	23
Allowed Remote IP (IP1;IP2;...)	0.0.0.0
HostName	FTA1101

Field Name	Description
User type	Choose the user type from admin user and normal user and basic user
New User Name	You can modify the user name, set up a new user name
New Password	Input the new password
Confirm Password	Input the new password again
Language	Select the language for the web, the device support Chinese, English, and Spanish and so on
Remote Web Login	Enable/Disable remote Web login
Web Port	Set the port value which is used to login from Internet port and PC port, default is 80
Web Idle timeout	Set the Web Idle timeout time. The webpage can be logged out after Web Idle Timeout without any operation
Allowed Remote IP(IP1,IP2,...)	Set the IP from which a user can login the device remotely

Telnet Port	Set the port value which is used to telnet to the device
-------------	--

NTP settings

Table 48 NTP settings

Time/Date Setting

NTP Settings

NTP Enable Enable ▼
Option 42 Disable ▼
Current Time 2016 - 01 - 19 . 05 : 55 : 06
Sync with host Sync with host
NTP Settings (GMT-06:00) Central Time ▼
Primary NTP Server pool.ntp.org
Secondary NTP Server
NTP synchronization(1 - 1440min) 60

Daylight Saving Time

Daylight Saving Time Disable ▼

Field Name	Description
NTP Enable	Enable/Disable NTP
Option 42	Enable/Disable DHCP option 42. This option specifies a list of the NTP servers available to the client by IP address
Current Time	Display current time
NTP Settings	Setting the Time Zone
Primary NTP Server	Primary NTP server's IP address or domain name
Secondary NTP Server	Options for NTP server's IP address or domain name
NTP synchronization	NTP synchronization cycle, cycle time can be 1 to 1440 minutes in any one, the default setting is 60 minutes

Daylight Saving Time

Table 49 Daylight Saving Time

Daylight Saving Time	
Daylight Saving Time	Enable ▼
Offset	60 Min.
Start Month	April ▼
Start Day of Week	Sunday ▼
Start Day of Week Last in Month	First in Month ▼
Start Hour of Day	2
Stop Month	October ▼
Stop Day of Week	Sunday ▼
Stop Day of Week Last in Month	Last in Month ▼
Stop Hour of Day	2

Procedure

Step 1. Enable Daylight Savings Time.

Step 2. Set value of offset for Daylight Savings Time

Step 3: Set starting Month/Week/Day/Hour in Start Month/Start Day of Week Last in Month/Start Day of Week/Start Hour of Day, analogously set stopping Month/Week/Day/Hour in Stop Month/Stop Day of Week Last in Month/Stop Day of Week/Stop Hour of Day.

Step 4. Press Saving button to save and press Reboot button to active changes.

System Log Setting

Table 50 System log Setting

System Log Setting	
Syslog Setting	
Syslog Enable	Enable ▼
Syslog Level	INFO ▼
Login Syslog Enable	Enable ▼
Call Syslog Enable	Enable ▼
Net Syslog Enable	Enable ▼
Device Management Syslog Enable	Enable ▼
Device Alarm Syslog Enable	Enable ▼
Kernel Syslog Enable	Enable ▼
Remote Syslog Enable	Disable ▼
Remote Syslog Server	

Field Name	Description
Syslog Enable	Enable/Disable syslog function
Syslog Level	Select the system log, there is INFO and Debug two grades, the Debug INFO can provide more information
Remote Syslog	Enable/Disable remote syslog function
Remote Syslog	Add a remote server IP address
Syslog Enable	Enable/Disable syslog function

Factory Defaults Setting

Table 51 Factory Defaults Setting

Factory Defaults Setting
Factory Defaults Setting Factory Defaults Lock Disable ▼
Description
When enabled, the device may not be reset to factory defaults until this parameter is reset to

Factory Defaults

Table 52 Factory Defaults

Factory Defaults
Reset to Factory Defaults Factory Default
Description
Click Factory Default to restore the residential gateway to factory settings

Firmware Upgrade

Table 53 Firmware upgrade

Status	Network	Wireless	SIP Account	Phone	Administration				
Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP	TR-069	Diagnosis	Operating	

Firmware Management
[Help](#)

Firmware Upgrade

Local Upgrade
 未选择任何文件

Description

1. Choose upgrade file type from Image File and Dial Rule
2. Press “Browse..” button to browser file
3. Press to start upgrading

Scheduled Tasks

Table 54 Scheduled Tasks

Status	Network	Wireless	SIP Account	Phone	Administration				
Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP	TR-069	Diagnosis		

Scheduled Tasks

Scheduled Wi-Fi

No.	Enable	SSID	Week Select	Open Time	Close Time
Delete Selected Add Edit					

Scheduled Reboot

Scheduled Reboot

Scheduled Mode

Time :

Scheduled PPPoE

Scheduled PPPoE

Scheduled Mode

Time :

Field Name	Description
Scheduled Reboot	
Scheduled Reboot	Enable/Disable scheduled Reboot
Scheduled Mode	Select scheduled Mode
Time	Set the time to restart

Scheduled PPPoE

Scheduled PPPoE	Enable/Disable scheduled PPPoE
Scheduled Mode	Select scheduled Mode
Time	Set the time to start PPPoE

Provision

Provisioning allows the router to auto-upgrade and auto-configure devices which support TFTP, HTTP and HTTPS .

- Before testing or using TFTP, user should have tftp server and upgrading file and configuring file.
- Before testing or using HTTP, user should have http server and upgrading file and configuring file.
- Before testing or using HTTPS, user should have https server and upgrading file and configuring file and CA Certificate file (should same as https server's) and Client Certificate file and Private key file

User can upload a CA Certificate file and Client Certificate file and Private Key file in the Security page.

Table 55 Provision

Status	Network	Wireless	SIP Account	Phone	Administration		
Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP	TR-069	Diagnosis
Provision							
Configuration Profile							
Provision Enable	Enable ▾						
Resync on Reset	Enable ▾						
Resync Random Delay (sec)	40						
Resync Periodic (sec)	3600						
Resync Error Retry Delay (sec)	3600						
Forced Resync Delay (sec)	14400						
Resync after Upgrade	Enable ▾						
Resync from SIP	Disable ▾						
Option 66	Enable ▾						
Option 67	Enable ▾						
Config File Name	\$(MA)						
User Agent							
Profile Rule	http://prv1.flyingvoice.net:69/config/\$(MA)?mac=\$(MA)&						
Field Name	Description						
Provision Enable	Enable provision or not.						

Resync on Reset	Enable resync after restart or not
Resync Random	Set the maximum delay for the request of synchronization file. The default
Resync	If the last resync was failure, The router will retry resync after the
Resync Error Retry	Set the periodic time for resync, default is 3600s
Forced Resync	If it's time to resync, but the device is busy now, in this case,the router
Resync After	Enable firmware upgrade after resync or not. The default is Enabled
Resync From SIP	Enable/Disable resync from SIP
Option 66	It is used for In-house provision mode only. When use TFTP with option
Config File Name	It is used for In-house provision mode only. When use TFTP with option
Profile Rule	URL of profile provision file

Table 56 Firmware Upgrade**Firmware Upgrade**

Enable Upgrade	Enable ▼
Upgrade Error Retry Delay (sec)	3600
Upgrade Rule	

Field Name	Description
Upgrade Enable	Enable firmware upgrade via provision or not
Upgrade Error Retry Delay(sec)	If the last upgrade fails, the router will try upgrading again after “Upgrade Error Retry Delay” period, default is 3600s
Upgrade Rule	URL of upgrade file

SNMP

Table 57 SNMP

Status	Network	Wireless	SIP Account	Phone	Administration
Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP
TR-069	Diagnosis				

SNMP Configuration	
SNMP Configuration	
SNMP Service	Disable ▼
Trap Server Address	
Read Community Name	public
Write Community Name	private
Trap Community	trap
Trap Period Interval (sec)	300

Field Name	Description
------------	-------------

SNMP Service	Enable or Disable the SNMP service
Trap Server Address	Enter the trap server address for sending SNMP traps
Read Community Name	String value that is used as a password to request information via SNMP from the device
Write Community Name	String value that is used as a password to write configuration values to the device SNMP
Trap Community	String value used as a password for retrieving traps from the device
Trap period	The interval for which traps are sent from the device

TR-069

TR-069 provides the possibility of auto configuration of internet access devices and reduces the cost of management. TR-069 (short for Technical Report 069) is a DSL Forum technical specification entitled CPE WAN Management Protocol (CWMP). It defines an application layer protocol for remote management of end-user devices. Using TR-069, the terminals establish connection with the Auto Configuration Servers (ACS) and get configured automatically.

Device Configuration using TR-069

The TR-069 configuration page is available under Administration menu.

Table 58 TR069

Status	Network	Wireless	SIP Account	Phone	Administration
Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP
TR-069	Diagnosis				

TR-069 Configuration

ACS

TR-069 Enable

Enable ▼

CWMP

Enable ▼

ACS URL

http://acs1.flyingvoice.net:8080/tr069

User Name

EZN0000004

Password

.....

Enable Periodic Inform

Enable ▼

Periodic Inform Interval

75724

Connect Request

User Name

FTA1101

Password

.....

Field Name	Description
ACS parameters	
TR069 Enable	Enable or Disable TR069

CWMP	Enable or Disable CWMP
ACS URL	ACS URL address
User Name	ACS username
Password	ACS password
Periodic Inform	Enable the function of periodic inform or not. By default it is Enabled
Periodic Inform	Periodic notification interval with the unit in seconds. The default value is
Connect Request parameters	
User Name	The username used to connect the TR069 server to the DUT.
Password	The password used to connect the TR069 server to the DUT.

Diagnosis

In this page, user can do packet trace, ping test and traceroute test to diagnose the device's connection status.

Table 59 Diagnosis

Management	Firmware Upgrade	Scheduled Tasks	Certificates	Provision	SNMP	TR-069	Diagnosis
------------	------------------	-----------------	--------------	-----------	------	--------	-----------

Packet Trace

Packet Trace

Tracking Interface: WAN
Filtering Rule: ALL Packets
Upload Packet Enable: Disable
Packet Trace: start stop save

Ping Test

Ping Test

Dest IP/Host Name:
WAN Interface: 1_MANAGEMENT_VOICE_INTERNET_R_VID_

Traceroute Test

Traceroute Test

Dest IP/Host Name:
WAN Interface: 1_MANAGEMENT_VOICE_INTERNET_R_VID_

Description

1. Packet Trace

Users can use the packet trace feature to intercept packets which traverse the device. Click the Start button to start home gateway tracking and keep refreshing the page until the message trace shows to stop, click the Save button to save captured packets.

2. Ping Test

Enter the destination IP or host name, and then click Apply, device will perform ping test.

Ping Test

Ping Test

Dest IP/Host Name:

WAN Interface:

```

PING www.baidu.com (115.239.210.26): 56 data bytes
64 bytes from 115.239.210.26: seq=0 ttl=54 time=43.979 ms
64 bytes from 115.239.210.26: seq=1 ttl=54 time=53.875 ms
64 bytes from 115.239.210.26: seq=2 ttl=54 time=45.226 ms
64 bytes from 115.239.210.26: seq=3 ttl=54 time=49.534 ms
64 bytes from 115.239.210.26: seq=4 ttl=54 time=49.045 ms

--- www.baidu.com ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
round-trip min/avg/max = 43.979/48.331/53.875 ms
  
```

3. Traceroute Test

Enter the destination IP or host name, and then click Apply, device will perform traceroute test.

Traceroute Test

Traceroute Test

Dest IP/Host Name:

WAN Interface:

```

traceroute to www.google.com (216.58.208.68), 30 hops max, 38 byte packets
 1  10.110.134.254 (10.110.134.254)  1.017 ms  9.507 ms  1.419 ms
 2  * * *
 3  * * *
 4  * * *
 5  * * *
 6  * * *
 7  * * *
 8  * * *
 9  * * *
10  * * *
  
```

Apply Cancel

Chapter 5 IPv6 address configuration

The router devices support IPv6 addressing. This chapter covers:

- [Introduction](#)
- [IPv6 Advance](#)
- [Configuring IPv6](#)
- [Viewing WAN port status](#)
- [IPv6 DHCP configuration for LAN/WLAN clients](#)
- [LAN DHCPv6](#)

Introduction

DHCPv6 protocol is used to automatically provision/configure IPv6 capable end points in a local network. In addition to acquiring an IPv6 IP address for the WAN interface and its associated LAN/WLAN clients, the devices are also capable of prefix delegation.

The Routers devices support the following types of modes of IPv6 addresses:

- Stateless DHCPv6
- Statefull DHCPv6

Table 63 IPv6 Modes

Mode	Description
Stateless	In Stateless DHCPv6 mode, the Routers devices listen for ICMPv6 Router Advertisements messages which are periodically sent out by the routers on the local link or requested by the node using a Router Advertisements solicitation message. The device derives a unique IPv6 address using prefix receives from the router and its own MAC address.
DHCPv6 Server (ROUTER) R201 PC R200	
Statefull	In Statefull DHCPv6 mode, the client works exactly as IPv4 DHCP, in which hosts receive both their IPv6 addresses and additional parameters from the

IPv6 Advance

To enable IPv6 functionality:

Navigate to Network > IPv6 Advanced page.

Select Enable from the IPv6 Enable drop-down list.

Click Save.

Table 64 Enabling IPv6

Configuring IPv6

Configuring Statefull IPv6

1. Navigate to Network > IPv6WAN page. The following window is displayed:

Table 65 Configuring Statefull IPv6

Field Name	Description
Connection Type	Select connection type
DHCPv6 Address	Set it to statefull mode.
Prefix Delegation	Select Enable.

Viewing WAN port status

To view the status of WAN port:
Navigate to Status page.

Network Status	
Active WAN Interface	
Connection Type	DHCP
IP Address	192.168.10.174 Renew
Link-Local IPv6 Address	
Subnet Mask	255.255.255.0
Default Gateway	192.168.10.1
Primary DNS	192.168.10.1
Secondary DNS	192.168.18.1
IPv6 PD Prefix	
IPv6 Domain Name	
IPv6 Primary DNS	
IPv6 Secondary DNS	
WAN Port Status	100Mbps Full

IPv6 DHCP configuration for LAN/WLAN clients

Wired and wireless clients connected to the Routers can obtain their IPv6 addresses based on how the LANs

ide DHCPv6 parameters are configured. The Routers can be either configured as a DHCPv6 server in which the

LAN/WLAN clients get IPv6 addresses from the configured pool.If DHCP server is disabled on the Routers, the

clients will get IPv6 addresses from the external DHCPv6 server configured in the network.

, the LAN/WLAN clients of Routers can be configured to receive IPv6 addresses from locally configured IPv6 pool or from an external DHCPv6 server.

, To enable LAN DHCPv6 service:

Status	Network	SIP	FXS1	FXS2	Administration
WAN	LAN	IPv6 Advanced	IPv6 WAN	IPv6 LAN	VPN
DMZ	DDNS	Port Setting	Routing		

IPv6 LAN Setting

IPv6 LAN Setting

IPv6 Address	fec0::1
IPv6 Prefix Length	64 (0-128)
DHCPv6 Server	
DHCPv6 Status	Disable
DHCPv6 Mode	Stateless
Domain Name	
Server Preference	255 (0-255)
Primary DNS Server	
Secondary DNS Server	
Lease Time	86400 (0-86400sec)
IPv6 Address Pool	- /
Router Advertisement	
Router Advertisement	Disable
Advertise Interval	30 (10-1800sec)
RA Managed Flag	Disable
RA Other Flag	Enable
Prefix	/
Prefix Lifetime	3600 (0-3600sec)

Chapter 6 Troubleshooting Guide

This chapter covers:

- [Configuring PC to get IP Address automatically](#)
- [Cannot connect to the Web GUI](#)
- [Forgotten Password](#)

Configuring PC to get IP Address automatically

Follow the below process to set your PC to get an IP address automatically:


Step 1 : Click the “Start” button

Step 2 : Select “control panel” , then double click “network connections” in the “control panel”

Step 3 : Right click the “network connection” that your PC uses, select “attribute” and you can see

the interface as shown in Figure 3.

Step 4.: Select “Internet Protocol (TCP/IP)” , click “attribute” button, then click the “Get IP address automatically” .



Cannot connect to the Web

Solution:

- Check if the Ethernet cable is properly connected
- Check if the URL is correct. The format of URL is: http:// the IP address
- Check on any other browser apart from Internet explorer such Google
- Contact your administrator, supplier or ITSP for more information or assistance.

Forgotten Password

If you have forgotten the management password, you cannot access the configuration web GUI.

Solution:

To factory default: press and hold reset button for 10 seconds.